

IN THE CLAIMS

Please amend the claims, as follows:

1. (original)A beverage brewer, comprising:
 - an operator control panel with a plurality of hidden function selection switches respectively associated with a plurality of different operator selectable brewer functions;
 - means for preselecting different modes of operation; and
 - a controller with means for selectively revealing only preselected ones of the hidden function switches to an operator in accordance with the different preselected modes of operation.
2. (currently amended)The beverage brewer of claim 1 in which
 - some of the plurality of different operator selectable brewer functions ~~include a function of starting brew cycles for making different quantities of beverage, and~~
 - the different preselected modes of operation are respectively associated with making the different quantities of beverage.
3. (original)The beverage brewer of claim 2 in which the different quantities of beverage associated with the different modes of operation include relatively small, medium and large batch sizes.
4. (original)The beverage brewer of claim 3 in which the controller includes means for preselecting more than one of the different modes of operation.
5. (currently amended)The beverage brewer of claim 1 in which
 - the control panel has other hidden switches associated with other functions, and
 - the controller has means for selectively revealing the other hidden switches regardless of the different preselected modes of operation.

6. (original)The beverage brewer of claim 5 in which the other functions include at least one of a brewer power-on function, a stop brew cycle function and a water dispense function.
7. (original)The beverage brewer of claim 5 in which the controller includes
means for preselecting the different modes of operation, and
means for enabling operation of the different modes of operation in response to actuation of the associated preselected ones of the revealed hidden function switches.
8. (original)The beverage brewer of claim 5 in which the means for preselecting include means responsive to actuation of at least one of the other function switches to program the controller.
9. (original)The beverage brewer of claim 5 in which the operator control panel has a message display for displaying information related to making preselections of the different modes of operation.
10. (original)The beverage brewer of claim 9 in which
the message display is a hidden message display, and
the controller has means for selectively revealing the message display when the preselections related information is needed for making preselections.
11. (original)The beverage brewer of claim 1 in which
the control panel includes a hidden message display, and
the controller includes means for selectively revealing at least a portion of the hidden message display.
12. (original)The beverage brewer of claim 11 in which
the control panel includes another brewer function switch that is revealed regardless of the operating mode for programming the operation of the brewer, and
the controller includes means for revealing the message display only when there is

a message to be displayed.

13. (original) The beverage brewer of claim 12 in which the means for enabling the message display to be revealed includes another hidden function switch that is revealable regardless of the different modes that have been preselected.

14. (currently amended) The beverage brewer of claim 1 in which
the operator control panel includes at least another hidden function selection switch associated with at least another brewer function that is independent of the different modes of operation, and

the controller includes means for selectively revealing the at least another hidden function selection switch in response to a change in operating conditions of the brewer.

15. (currently amended) The beverage brewer of claim 14 in which

the other ~~brewer~~ hidden function selection switch is associated with an emergency stop brew cycle function, and

said controller selectively revealing means reveals the emergency stop brew function only when the brewer is in a brew cycle.

16. (original) The beverage brewer of claim 14 in which

the another brewer function switch is associated with a hot water dispense function in which hot water is dispensed from a dispense nozzle, and

said controller selectively revealing means reveals the hot water dispense function only when the brewer is not operating in a brew cycle.

17. (original) The beverage brewer of claim 14 in which

the other brewer function switch is associated with a full power on function, and
said controller selectively revealing means reveals the full power on switch only when the full power is off.

18. (original) The beverage brewer of claim 1 in which

the plurality of function switches are associated with a plurality of start brew functions for making different quantities of beverage, and

the controller includes means for revealing only the preselected one of the hidden function switches when the brewer is not already in a brew cycle.

19. (currently amended) The beverage brewer of claim 1 in which the plurality of hidden function switches are respectively associated with ~~start~~starting of a plurality of different brew cycles associated with a plurality of different quantities of beverage to be brewed and the controller includes means for selectively revealing only the preselected ones of the hidden function switches when a brew cycle is not already in progress.

20. (original) The beverage brewer of claim 1 including

a partially translucent panel through which the hidden function switches cannot be seen under ordinary ambient light conditions behind which the hidden function switches are located, and in which

the selectively revealing means includes

a plurality of lights each associated with at least one of each of the hidden function switches, and

means for selectively energizing the lights associated with the hidden function switches selected to be revealed to light portions of the partially translucent panel adjacent the selected function switches, said light being visible through the translucent panel to indicate the location of the selected function switch.

21. (original) The beverage brewer of claim 20 in which the function selection switches are push button switches and the partially translucent panel is sufficiently flexible to enable actuating the push button brewer function switches by pushing against the panel opposite the switches to press the panel against the push button switches.

22. (currently amended) The beverage brewer of claim 21 in which the push_button switches have means for carrying the associated light that is energized by the revealing means to reveal the location of the push_button switch.

23. (currently amended) The beverage brewer of claim 20 in which each of the plurality of lights is associated with only one of the hidden ~~brewer~~ function selection switches.

24. (original) The beverage brewer of claim 20 in which the plurality of lights is a plurality of light emitting diodes.

25. (original) The beverage brewer of claim 24 in which the plurality of lights is a plurality of incandescent light bulbs.

26. (currently amended) A beverage brewer, comprising:

an operator control panel with a plurality of hidden function selection switches respectively associated with a plurality of different operator selectable brewer functions; and

a controller with means for selectively revealing only selected ones of the hidden function selection switches to an operator in accordance with different phases of operation of the brewer.

27. (currently amended) The beverage brewer of claim 26 in which

some of the plurality of different operator selectable brewer functions include functions of starting brew cycles for making different quantities of beverage, and

the controller selectively reveals ~~the~~ start brew cycle function selection switches only when the operating status is other than a brewing-in-process status.

28. (currently amended) The beverage brewer of claim 26 in which the brewer functions include at least one of (a) a brewer power on function, (b) a stop brew cycle function, and (c) a water dispense function and (d) a start brew function.

29. (currently amended) The beverage brewer of claim 26 in which

the controller includes means for programming the controller to operate in different modes of operation, and

at least one of the function selection switches is also capable of being used for inputting programming information.

30. (original) The beverage brewer of claim 29 in which the operator control panel has a message display for displaying information needed for programming the controller.

31. (original) The beverage brewer of claim 30 in which
the message display is a hidden message display, and
the controller has means for selectively revealing the message display when needed for programming.

32. (original) The beverage brewer of claim 26 in which
the control panel includes a hidden message display, and
the controller includes means for selectively revealing at least a portion of the hidden message display.

33. (original) The beverage brewer of claim 32 in which the controller includes means for revealing the message display only when there is a message to be displayed.

34. (currently amended) The beverage brewer of claim 26 in which
one of the brewer function switches an emergency stop brew switch is associated with an emergency stop brew cycle function, and
said controller selectively revealing means reveals the emergency stop brew functions switch only when the brewer is in a brew cycle.

36. (currently amended) The beverage brewer of claim 26 in which
one of the brewer function switches is a hot water dispense switch associated with a hot water dispense function in which hot water is dispensed from a dispense nozzle, and

said controller selectively revealing means reveals the hot water dispense function switch only when the brewer is not operating in a brew cycle.

37. (currently amended) The beverage brewer of claim 26 in which

another brewer function switch is a full power on switch associated with a full power-on function, and

said controller selectively revealing means reveals the full power on switch only when the full power is off.

38. (currently amended) The beverage brewer of claim 26 in which

at least one of the plurality of function switches is a start brew switch associated with a start-brew function for making an associated quantity of beverage, and

the controller includes means for revealing the start brew ~~function~~ switch only when the brewer is not already in a brew cycle.

39. (currently amended) The beverage brewer of claim 38 in which

at least another one of the plurality of function switches is another start brew switch associated with a start brew function for making another associated quantity of beverage different from the one quantity of beverage, and

the controller includes means for revealing both the one and the other hidden start brew switch when the brewer is not already in a brew cycle.

40. (currently amended) The beverage brewer of claim 39 in which the controller includes

means for preselecting different modes of operation in which less than all of the one and the other brew start switches are enabled to start a brew cycle, and

means for selectively disabling the revealing means from revealing any of the one and the other hidden brew start switches that is not enabled.

41. (currently amended) The beverage brewer of claim 26 in which

the hidden function selection switches are hidden behind a partially translucent panel through which the hidden function selection switches cannot be seen under ordinary ambient light conditions. and

the selectively revealing means includes means for selectively lighting portions of the the panel adjacent the hidden function selection switches selected to be revealed, light from said selectively lighting means being visible through the translucent panel to indicate the location of the selected function selection switch.

42. (currently amended)The beverage brewer of claim 41 in which

the function selection switches are push button switches, and

the partially translucent panel is sufficiently flexible to enable actuating the push button ~~brewer-function~~ switches by pushing against the panel opposite the push button switches to press the panel against the push button switches.

43. (currently amended)The beverage brewer of claim 42 in which the pushbutton switches have means for carrying a source of light that is energized by the revealing means to reveal the location of the push_button switch.

44. (currently amended)The beverage brewer of claim of claim 42 in which the selectively lighting means includes a separate light source for each of the push button ~~brewer-function~~ switches.

45. (original)The beverage brewer of claim 44 in which each light source includes at least one light emitting diodes.

46. (original)The beverage brewer of claim 44 in which each light source is at least one incandescent light source.

47. -90. (cancelled)

91. (original) In a food processing apparatus for performing a plurality of processes on a food ingredient, the improvement being a directive manual control system, comprising:

a plurality of hidden function selection switches associated with a plurality of different operator selectable food processing functions;

a housing with a partially translucent, protective, operator control panel having an interior side covering the plurality of switches and through which the hidden function switches cannot be seen under ordinary ambient light conditions, and an exterior side for manual engagement by an operator;

a plurality of lights each associated with at least one of each of the hidden function switches and located at the interior side of the panel;

a controller with means for selecting ones of the hidden function switches to be revealed to an operator in accordance with a computer program stored in the controller; and

means for energizing only the lights associated with the hidden function selection switches selected to be revealed to illuminate portions of the interior side partially translucent panel adjacent the selected function switches, said illumination of the interior side of the panel being visible through the translucent panel to indicate at the exterior of the panel the location of the selected one of the function switches.

91. (canceled)

92. (currently amended) The food processing apparatus of claim ~~94~~123 in which the controller when in the preselected different modes of operation relatively temporarily disables different ones of the function selection switches that are not relatively permanently disabled in response to changing conditions of the apparatus.

93. (currently amended) The food processing apparatus of claim ~~94~~123 in which the different modes of operation include different modes of operation of one of (a) a coffee brewer, (b) a hot tea brewer, (c) a fresh iced tea brewer, (d) a hot water heater and dispenser and (e) a food grinder.

94.-96. (canceled)

97. (currently amended) In a food processing apparatus for performing a plurality of processes on a food ingredient, the improvement being a directive manual control system, comprising:

a plurality of hidden function selection switches associated with a plurality of different operator selectable food processing functions;

a housing with a partially translucent, protective, operator control panel having an interior side covering the plurality of switches and through which the hidden function switches cannot be seen under ordinary ambient light conditions, and an exterior side for manual engagement by an operator with a tactile code associated with at least one of the plurality of switches;

a plurality of lights each associated with at least one of each of the hidden function selection switches and located at the interior side of the panel;

a controller with means for selecting ones of the hidden function selection switches ~~switches~~ to be revealed to an operator in accordance with a computer program stored in the controller; and

means for energizing only the lights associated with the hidden function selection switches selected to be revealed to illuminate portions of the interior side partially translucent panel adjacent the selected function switches, said illumination of the interior side of the panel being visible through the translucent panel to indicate at the exterior of the panel the location of the selected one of the function switches; ~~and~~

98. (original) The food processing apparatus of claim 97 in which the tactile code is formed by embossments formed on the exterior side of the exterior side of the surface of the operator control panel.

99. (original) The food processing apparatus of claim 97 in which the tactile code is a Braille code.

100. (original) In a food processing apparatus for performing a plurality of processes on a food ingredient, the improvement being a directive manual control system, comprising:

a plurality of hidden function selection switches associated with a plurality of different operator selectable food processing functions; and

a housing with a partially translucent, protective, operator control panel having an interior side covering the plurality of switches and through which the hidden function switches cannot be seen under ordinary ambient light conditions, and an exterior side for manual engagement by an operator with a tactile code associated with at least one of the plurality of switches.

101. (currently amended) In a food processing apparatus for performing a plurality of processes on a food ingredient including a heating element and a plurality of valves, the improvement being a manual control system, comprising:

a plurality of hidden function selection switches associated with a plurality of different operator selectable food processing functions including functions associated with the plurality of valves;

a housing with a partially translucent, protective, operator control panel having an interior side covering the plurality of switches and through which the hidden function switches cannot be seen under ordinary ambient light conditions, and an exterior side for manual engagement by an operator;

a plurality of lights each associated with at least one of each of the hidden function switches and located at the interior side of the panel;

a controller with means for selecting ones of the hidden function switches to be revealed to an operator in accordance with a computer program stored in the controller; and

means for energizing only the lights associated with the hidden function selection switches selected to be revealed to illuminate portions of the interior side partially translucent panel adjacent the selected function switches, said illumination of the interior side of the panel being visible through the translucent panel to indicate at the exterior of the panel the location of the selected one of the function switches; and

means associated with the controller for providing a demonstration mode in which the heating elements and all of the plurality of valves are disabled from operating in response to actuation of the hidden function switches but in which the controller selectively reveals the hidden function selection switches and operates otherwise substantially the same in response to actuation of the function selections switches and the computer program stored in the controller.

102. (currently amended) In a food processing apparatus for performing a plurality of processes on a food ingredient including a heating element and a plurality of valves, the improvement being a manual control system, comprising:

means for selectively operating the apparatus in accordance with a normal operations ~~mode program~~ in which the heating element and the plurality of valves may be operated in accordance with ~~the~~ normal operations program; and

means for selectively operating the apparatus in accordance with one of

a program mode in which various programmable parameters that dictate operation in the normal operations program may be selectively excluded and other parameters may be established;

~~_____ means for selectively operating the apparatus for operation in accordance with a self-diagnostic mode self-diagnostic program~~ in which faults in the apparatus are detected and displayed; and

~~_____ means for operating the apparatus in accordance with a demonstration mode~~ substantially the same as the normal operations mode except for selected functions.

103. (original) The food processing apparatus of claim 102 in which the apparatus includes an electronic message display that is operated in accordance with one of the program mode, the self-diagnostic mode and the demonstration mode of operation.

104. (currently amended) The food processing apparatus of claim 102 including a plurality of hidden switches that are selectively revealed by back-lights ~~during~~ when in the normal operations program, and

means for disabling selective function normally performed during normal operations of the apparatus when in the demonstration mode of operation while continuing to enable substantially all other normal operations of the apparatus including selective revealing of the hidden switches ~~and in~~ response of the back-lights.

105. (original) The food processing apparatus of claim 102 in which the apparatus includes an electronic display that is operated in accordance with the self-diagnostic program to display error codes associated with different fault conditions that are detectable by the self-diagnostic program.

106. (new) The beverage brewer of claim 1 in which the hidden function switches are discrete switches that are spaced from one another at fixed locations.

107. (new) The beverage brewer of claim 26 in which the hidden function switches are discrete switches that are spaced from one another at fixed locations.

108. (new) The beverage brewer of claim 91 in which the hidden function switches are discrete switches that are spaced from one another at fixed locations.

109. (new) The beverage brewer of claim 97 in which the hidden function switches are discrete switches that are spaced from one another at fixed locations.

110. (new) The beverage brewer of claim 100 in which the hidden function switches are discrete switches that are spaced from one another at fixed locations.

111. (new) The beverage brewer of claim 101 in which the hidden function switches are discrete switches that are spaced from one another at fixed locations.

112. (new) The beverage brewer of claim 1 in which the hidden switches are associated with only a single function.

113. (new) The beverage brewer of claim 26 in which the hidden switches are associated with only a single function.

114. (new) The beverage brewer of claim 91 in which the hidden switches are associated with only a single function.

115. (new) The beverage brewer of claim 97 in which the hidden switches are associated with only a single function.

116. (new) The beverage brewer of claim 100 in which the hidden switches are associated with only a single function.

117. (new) The beverage brewer of claim 101 in which the hidden switches are associated with only a single function.

118. (new) The beverage brewer of claim 11 in which the message display is distinct and separated from the function selection switches.

119. (new) The beverage brewer of claim 11 in which the message display is an LED display.

120. (new) The beverage brewer of claim 32 in which the message display is distinct and separated from the function selection switches.

122. (new) The beverage brewer of claim 32 in which the message display is an LED display.

123 (previously presented) The food processing apparatus of claim 91 including means associated with the controller for preselecting different modes of operation in which different ones of the function switches are not to be used and means for relatively

permanently disabling the different ones of the function switches not to be used while the associated mode of operation remains preselected.

124. (new) The food processing apparatus of claim 102 including means for selectively hiding the electronic message display during operations in accordance with the normal operations programs and selectively revealing the electronic message display when the apparatus is operated in accordance with the at least one of the program mode, the self-diagnostic mode and the demonstration mode.

125. (new) The food processing apparatus of claim 103 in which the electronic display is selectively revealed during all of the program mode, the self-diagnostic mode and the demonstration mode.